

# Your powerhouse built for high-speed output and rock-solid reliability.

Designed for intense demands of high volume environments, the TASKalfa MZ10500i delivers exceptional speed, durability, and workflow efficiency. Its 300-ipm AI-enhanced scanning accelerates document capture, while 105 prints per minute output keeps production on schedule. The innovative dual-toner system ensures continuous operation with minimal intervention.



## **TASKalfa MZ10500i**



**Cloud Ready A3  
Monochrome Multifunctional**

**Up to 105 pages A4 per minute**

**Cutting-edge 300 ipm,  
AI-enabled and Straight path scanner**

**Flexible paper handling up to SRA3**

**Space saving hybrid finisher**

# TASKalfa MZ10500i

## GENERAL

**Technology:** Laser, Monochrome, HyPAS™ solution platform  
**Operation panel:** 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel mounted and 90° rotatable  
**Engine speed:** Up to 105 pages A4 per minute; Up to 52 pages A3 per minute;  
**Duplex print speed:** 105 page per minute, A4  
**Resolution:** 1200 x 1200 dpi; 600 x 600 dpi (scan/copy)  
**Warm-up time:** Approx. 50 seconds or less  
**Time to first print:** Approx. 3.9 seconds or less  
**Time to first copy:** Approx. 3.5 seconds or less, Approx. 4.3 seconds or less (Platen)  
**CPU:** QoriQ LS1046A (Quad Core) 1.6 GHz  
**Memory:** Standard 7GB + 256GB SSD, Optional 1TB HDD  
**Standard interface:** USB 3.0 (Super-Speed USB), 4 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPsec, 802.3az support), optional Wi-Fi (IEEE 802.11a/b/g/n/ac), 2 eKUIO slots for optional internal print server or for optional fax system, slot for optional Wireless LAN, Slot for optional SD Card, NFC tag  
**Dimensions (W x D x H):** 685 x 660 x 1,227 mm  
**Weight:** Approx. 152 kg  
**Power source:** AC 220 ~ 240 V, 50/60 Hz  
**Power consumption:** Print/Copy: 1,530W; Ready Mode: 130W; Low power Mode: 120W Sleep Mode: 0.5W  
**Noise:** Copying/Printing Mode: 57.9 dB(A) LpA Stand-by: 44.4 dB(A) LpA (surface sound pressure level: ISO 7779 measurement distance of 1 meter)  
**Safety standards:** TÜV/GS, CE<sup>1</sup>

## PAPER HANDLING<sup>2</sup>

**Input capacity:** Multi-purpose tray: 250 sheets; 52 - 300g/m<sup>2</sup>, (Banner 136-163 g/m<sup>2</sup>); A6R - SRA3 (320 x 450 mm), Custom (89 x 127 to 297 x 432 mm), Banner max. 330.2 x 1,220 mm  
**Standard universal paper cassette:** 2 x 550 sheet; 52 - 300g/m<sup>2</sup>; Upper cassette A6R up to A3, lower cassette A6R up to SRA3; High-capacity paper deck: 2 x 1,500 sheets 52 - 300g/m<sup>2</sup>; A4, B5  
**Max. input capacity with options:** 7,850 sheets A4  
**Duplex:** Standard; 52 to 256 g/m<sup>2</sup> ~ A4 to A5R; 60 to 256 g/m<sup>2</sup> ~ SRA3 to A3  
**Output capacity:** Standard job separator tray 70 sheets, optional copy tray (D): upper 100 sheets, lower 250 sheets; max. optional output capacity 4,300 sheets

## PRINT FUNCTIONS

**Emulations:** PCL6 (PCL5e / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, PPM, XJDF/XJMF, XPS Direct Print and OpenXPS  
**Operating systems:** All current Windows operating systems MAC OS X Version 10.9 or higher; Unix, Linux as well as other operating systems on request  
**Fonts/barcodes:** 93 outline fonts (PCL6), 136 fonts (KPDL 3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 79 Outline Fonts; 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)  
**Print features:** Encrypted PDF 2.0 Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality, Super Resolution  
**Mobile printing support:** AirPrint, Mopria, NFC, Direct Wi-Fi (optional), MyPanel and KYOCERA Mobile Print app for iOS and Android, Microsoft Cloud printing

## COPY FUNCTIONS

**Max. original size:** A3/Ledger  
**Continuous copying:** 1-9999  
**Zoom range:** 25-400% in 1% steps  
**Pre-set magnification ratios:** 5 Reductions / 5 Enlargements  
**Exposure mode:** Auto, manual: 17 steps  
**Image adjustments:** Text + Photo, Photo, Text, Graphic/Map  
**Features:** Scan-once-copy-many, electronic sort, 2in1, 4in1, 8in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, Skip blank page, ID card copy, Confidential Document Guard

## SCAN FUNCTIONS

**Functionality:** Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.1.1, Scan-to-USB Host, Scan-to-box, Network TWIN, WSD scan (WIA Driver Network), DFS Scan, Straight path scan for thick and special media (cards), Scan to Cloud Storages (OneDrive, SharePoint, Google Drive, KClIM) with KCC (Kyocera Cloud Capture, Scan to Cloud application)  
**Scan speed:** 300 ipm duplex, 150 ipm simplex (300 dpi, A4)  
**Scan resolution:** 600, 400, 300, 200 dpi, 256 greyscales per colour (1,200 dpi via TWIN and WIA driver only) 256 greyscales per colour  
**Max. scan size:** A3, Ledger, Banner up to 2,200 mm  
**Original recognition:** Text, photo, text + photo, Light Text / Fine Line, optimised for OCR  
**File types:** TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF, MS Office file  
**Features:** Colour scan, Auto Colour Select, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip, Specified colour removal, Handwriting erase and highlight, Image Defect Prevention, ID scan

## FAX FUNCTIONS (OPTIONAL)

**Compatibility:** ITU -T Super G3  
**Modem speed:** Max. 33.6 kbps  
**Transmission speed:** Less than 3 seconds (JBIG)  
**Scanning speed:** 2.0 seconds or less  
**Address book:** 2000 entries  
**Fax resolution:** Normal: 200 x 100 dpi, Fine: 200 x 200 dpi, Superfine: 200 x 400 dpi, Ultrafine: 400 x 400 dpi, 600 x 600 dpi  
**Maximum original size:** A3, Ledger, Banner up to 1,600 mm  
**Compression method:** JBIG, MMR, MR, MH  
**Features:** Network faxing, rotate transmission, rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broadcast, Optional Internet-fax, dual fax with second fax system 14

## CONSUMABLES<sup>3</sup>

**Toner Kit:**  
**TK-6835;** 2 x Microfine toner black for 40,000 pages A4 (Max. machine capacity 80,000 pages A4)  
**Waste Toner Bottle:** WT-8830; 150,000 pages or more  
**Staple:** SH-10, 5000 x 3 staples, for BF-7200; SH-12, 5000 x 3 staples, for DF-7200; SH-15, 5000 x 5 staples, for DF-7210

## OPTIONS

**Cloud Ready Device with available applications<sup>4</sup>:**  
**Kyocera Cloud Capture (KCC):** Scan to Cloud and Document Capture solution available on device, activation for Trial Plan required to use.  
**Kyocera Cloud Print and Scan (KCPS):** Print Management, Cost Control and Security solution  
**Kyocera Cloud Information Manager (KClIM):** Document Management solution for document digitisation for smarter workplaces.  
**Fax System:** Fax System 14  
**Internet Fax Kit (A):** Internet Fax Kit (A) AC  
**DT-730(B):** Document table  
**Copy Tray(D):** Upper tray 100 sheets, lower tray 250 sheets  
**PF-7200:** Side Deck: 3,000 sheets, A4, 60-300 g/m<sup>2</sup>  
**PF-7210:** Side Deck: 3,200 sheets A4(80 g/m<sup>2</sup>), A6R-SRA3, 52-300 g/m<sup>2</sup>  
**DF-7200:** Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-7200 attachment); max. 52 - 300 g/m<sup>2</sup>; max. B5R - SRA3, Sub-tray: 200 sheets A4; 52 - 300 g/m<sup>2</sup>; A6R - SRA3, Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5 - 305 x 457 mm  
**DF-7210:** Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-7200 attachment); max. 52 - 300 g/m<sup>2</sup>; max. B5R - SRA3, Sub-tray: 200 sheets A4; 52 - 300 g/m<sup>2</sup>; A6R - SRA3, Stapling up to 100 sheets A4 or 50 sheets A3 at 3 positions, B5 - 305 x 457 mm  
**ZF-7200:** Z-folding, Bi-folding, Inner and Outer tri-folding, Engineering fold (Finisher is required)  
**IS-7200:** Inserter, Cover and Backing sheet insertion, 52-300 g/m<sup>2</sup>, A5-SRA3 (Finisher is required)  
**PH-7220/PH-7230:** Punch unit for DF-7200 and DF-7230, 2-hole/4-hole/Swedish type, 52-300 g/m<sup>2</sup>, A5-SRA3  
**MT-7200:** Mailbox sorter for DF-7200 and DF-7210, 7 bins x 100 sheets A4, 50 sheets A3/B4, 60-163 g/m<sup>2</sup>  
**BF-7200:** Booklet and tri-folding unit for DF-7200 and DF-7210  
**Banner Guide 12:** Banner paper feeding guide, 10 sheets  
**HD-16:** HDD 1 TB  
**NK-7120B:** Numeric keypad  
**Keyboard Holder 10**  
**UG-33 AC:** ThinPrint support  
**UG-34 AC:** Emulation (IBM Proprinter/EPSON LQ-850 LinePrinter)  
**USB IC Card Reader + Card Authentication Kit (B) AC**  
**IB-37:** Wireless Network Interface (USB : 5GHz/2.4GHz)  
**IB-38:** Wireless Network Interface (USB : 2.4GHz)  
**IB-51/55:** Wireless LAN Interface (802.11b/g/n)  
**IB-54:** Wireless LAN 5GHz/2.4GHz (IEEE802.11a/b/g/n/ac)  
**IB-53:** GB-Ethernet board 10 BaseT/100 BaseTX/1,000 BaseT

\*1. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

\*2. All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

\*3. Average continuous toner yield in accordance with 6% coverage A4.

\*4. Options and functionalities vary depending on the solution plan.

Specifications and design are subject to change without notice.

For the latest on connectivity visit [kyoceradocumentsolutions.eu](http://kyoceradocumentsolutions.eu).

TASKalfa, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.



HyPAS™



Kyocera Document Solutions Partner

Kyocera Document Solutions Europe Management B.V.  
Beechavenue 27 \* 1119 RA, Schiphol-Rijk The Netherlands  
Tel +31 (0) 20-654-0000 — Fax +31 (0) 20-653-1256



[kyoceradocumentsolutions.eu](http://kyoceradocumentsolutions.eu)

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.  
©2026 Kyocera Document Solutions Europe Management B.V.